

TECHNICAL SPECIFICATIONS

CONFIGURATION

CCS

OUTPUT

Maximum charging current [A]

250

COMMUNICATION

Charging mode

IEC 61851-1
IEC 61851-23
IEC 61851-24
ISO 15118
DIN 70121

Protocol

OCPP 1.6-J
OCPP 2.0.1

GENERAL

Housing

Steel with galvanised coating

Protection rating

IP 54
IK 10

Overall dimensions
[H x W x D] [mm]

804 x 519 x 379

Weight [kg]

~60

Operating temperature
range [°C]

- 25 +45

Operating altitude [m.a.s.l.]

≤ 2000

Compliance with standards

CE
LVD 2014/35/UE
EMC 2014/30/UE
RED 2014/53/UE

EQUIPMENT

CONFIGURATION	CCS
---------------	-----

CONNECTORS

DC Connectors	CCS 9,5 m
---------------	-----------

HOUSING

Colour RAL 9016	✓
-----------------	---

RAL Colour (Other)	Option
--------------------	--------

Additional branding	Option
---------------------	--------

Anti-graffiti	Option
---------------	--------

Mounting pole	Option
---------------	--------

Cable reel	Option
------------	--------

INTERFACE

Signal column	Option
---------------	--------

COMMUNICATION

Ethernet	✓
----------	---

Catalog code	SBX -A010L0000C -9016
--------------	-----------------------------
